TECHNICAL DATA

ACETATE CLOTH TAPE Product Code: 1A025

P. LEO & CO LTD

P.O. Box 175 Fo Tan, Shatin, Hong Kong. Telephone: (852) 2604-8222 * Facsimile: (852) 2693-2093 E-mail: sales@pleo.com * Web Site: http://www.pleo.com



91 UL FILE #E126174

Description: 1A025(black & white) is a very tough acetate cloth coated with <u>rubber-resin</u> thermosetting

pressure sensitive adhesive. Extremely conformable, rough and absorbent surface. It is

better suited for varnish impregnation. Temperature rating up to 130°C.

Features/Benefits: Used in all types of fine wire coils and transformer where good strength characteristics,

fine electrical properties and non-corrosion are desired. In construction and repair of electrical and electronic equipment. Provides aesthetic appearance to bobbin coils.

Technical Details: PROPERTIES UNIT SPECIFICATION

TOTAL THICKNESS	mm	0.21 ± 0.02
TENSILE STRENGTH	kg/25mm	13
ELONGATION	%	6
ADHESION TO STEEL	kg/25mm	0.6
DIELECTRIC BREAKDOWN	kV	2.0
TEMPERATURE RATING	°C	130

Color: White / Black

Availability: Standard 25M roll, 3" core, width 725mm

Shelf Life: 6 months when storage at 23°C and 65% relative humidity



All Statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness there of is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury loss or damage direct or consequential arising out of the use of or "he inability to use the product. Before using users shall determine the suitability of the product for their intended uses and users assume all risk and liability whatsoever in connection there with.

