

LODESTONE PACIFIC



Phone: (800) 694-8089
www.lodestonepacific.com
E-mail: sales@lodestonepacific.com



Technical drawing of the TCM120-04 toroid. The top view shows a circular component with two central holes and four outer holes. Dimensions include: .064 [1.6] (hole diameter), 1.21 [30.7] (total diameter), .330 [8.4] (hole offset), 1.05 [26.7] (hole spacing), and .093 [2.4] (hole diameter). The side view shows a toroid with a central post. Dimensions include: .554 [14.1] (toroid height), .490 [12.4] (toroid width), .030 [.76] (post diameter), and .062 [1.6] (post height).

± .010 inches
[mm] Not to Scale

TCM120-04

Material: PET (Black)
UL Rating: UL94-VO, Class F
4 Terminals: Self Terminating
Package Method: Bulk in Polybags

Application: For horizontal mounting of toroids utilizing the toroids winding leads to terminate to the PCB. The toroid's leads pass through the holes to be soldered to the PCB. The center post is designed for use in common mode applications where winding separation is important.

Made in our China Factory

[Request a Sample](#)

[View Inventory](#)

[Request a Quote](#)

[Toroid Mount Selector](#)

[REACH Database](#)

[Coil Winder Database](#)